

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 August 2004 (26.08.2004)

PCT

(10) International Publication Number
WO 2004/072365 A1

(51) International Patent Classification⁷: **D21F 1/66**
(21) International Application Number:
PCT/FI2004/000058

(22) International Filing Date: 5 February 2004 (05.02.2004)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20030205 11 February 2003 (11.02.2003) FI

(71) Applicant (for all designated States except US): **METSO PAPER, INC.** [FI/FI]; Fabianinkatu 9 A, Helsinki FI-00130 (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **HIETANIEMI, Matti** [FI/FI]; Kanjoninreuna 8 A 2, Tampere FI-33720 (FI).

(74) Agent: **FORSSÉN & SALOMAA OY**; Eerikinkatu 2, Helsinki FI-00100 (FI).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD IN THE TREATMENT OF THE STOCK PASSED TO A HEADBOX OF A PAPER MACHINE OR EQUIVALENT



(57) Abstract: The invention relates to an apparatus in the treatment of the stock passed to a headbox of a paper machine or equivalent, in which the apparatus includes at least two stock chests (10a₁, 10a₂). The stock (M₁) from a first stock chest (10a₁) is passed along a line (a₁, a₂) to a hydrocyclone plant (20) in the short circulation of the paper machine or equivalent. An accept line (a₃) of the hydrocyclone plant is connected with a stock line (b₁) of the stock (M₂) fed from a second stock chest (10a₂), and a combined stock flow is passed along a line (b₂) to the headbox (100) of the paper machine or equivalent. The invention also relates to a method in the treatment of the stock passed to a headbox of a paper machine or equivalent.

4/pets

Apparatus and method in the treatment of the stock
passed to a headbox of a paper machine or equivalent

5

The invention relates to an apparatus and a method in the treatment of the stock
passed to a headbox of a paper machine or equivalent.

Centrifugal cleaning is needed in paper machines for separation of sand and
10 contaminants. With today's technology, the cleaning efficiency of centrifugal
cleaning deteriorates when the fibre consistency of the pulp suspension exceeds 1
%. This limits the increasing of the feed consistency of the stock to be fed to the
headbox. In practice, the slotted screen technique has made it unnecessary to use
centrifugal cleaning for separating reject fibres, such as shives. A hydrocyclone
15 plant is placed in the short circulation of the paper machine, where the flow rates
are high, as high as 2000 l/s. To be operative, centrifugal cleaning requires a
pressure difference of 120-150 kPa. In that connection, all (about 5) steps of the
hydrocyclone plant require pumps, which represent as much as about 25 % of the
energy consumption of the short circulation. At a flow rate of 2000 l/s, the power
20 consumption of centrifugal cleaning is about 1200 kW. A typical amount of fibre
reject from centrifugal cleaning is about 0.1 – 0.2 % of production. The loss of the
filler pigments coming with coated broke is at its worst about 0.5 % of machine
production.

25 A filler recovery system is often incorporated in connection with the centrifugal
cleaning of the short circulation. In addition to filler, the system must also process
other rejects, such as fibre reject and sand, coming from the short circulation. In
that case, the efficiency of the filler recovery system is not best possible.

Concepts are known in which the cleaning of the stock has been transferred from the short circulation to pulp lines. The consistency (about 3 %) of the broke system is, however, not suitable for separation of sand with hydrocyclones.

- 5 When centrifugal cleaning is in the pulp line (e.g. chemical pulp, DIP or TMP), these pulps need not be cleaned again any more, but the debris, sand and non-disintegrating coating sheets of paper coming to the broke system via pulpers should be treated by means of hydrocyclones.
- 10 By placing a hydrocyclone plant in accordance with the invention in a broke system line in the short circulation, the problem is solved. The fibre consistency in the headbox can be increased, when needed, to a level of over 2 % without the fibre consistency in the centrifugal cleaning exceeding the limit of 1 %.
- 15 The size and the energy consumption of the hydrocyclone plant would be only about one third of the present size and energy consumption. The size is determined based on the maximal broke percentage.

At the same time, better selectivity is achieved in the filler recovery process.

20

In the invention, a hydrocyclone plant is placed in a stock line which is in the short circulation and uses broke, and it is connected with another stock line, so that the bulk of the stock flow (the purer stock) bypasses centrifugal cleaning.

- 25 The proposal reduces the energy consumption of centrifugal cleaning by about 65 %, which means a saving of about 17 % in the energy need of the short circulation. On a large machine the saved power is about 800 kW.

- 30 The amount of reject from centrifugal cleaning is reduced to a fraction, which means that the amount of reject from centrifugal cleaning would be in its entirety less than 0.05 % of production. In practice, it could halve the amount of reject in

the area of the paper mill, thus reducing the handling capacity associated with fibre recovery.

5 The investment in equipment is reduced by about 65 % in centrifugal cleaning and by about 10 % in respect of the short circulation. A hydrocyclone plant is a subprocess that takes up much space. By means of the arrangement in accordance with the invention, the paper machine hall is shortened by 3 m, with the result that the saving in building costs is considerable.

10 In accordance with the invention, a system is formed that includes at least two stock chests. The first stock chest comprises a stock composition M_1 containing pulp that requires centrifugal cleaning before it is passed to the headbox of the paper machine. The stock composition M_1 contains broke pulp passed from the paper machine and, in addition, it can contain pulp coming from fibre recovery
15 and further mechanical pulp. The second stock chest comprises a stock composition M_2 containing pulp that has already undergone centrifugal cleaning, such as recycled fibre and/or chemical pulp and/or TMP. Thus, it does not contain any broke coming from the paper machine. In the arrangement in accordance with the invention, only the stock M_1 of the first stock chest is treated in the
20 hydrocyclone plant and at least one accept is passed from it into connection with a second stock chest line and its stock M_2 . There can be more stock chests than two.

The apparatus in accordance with the invention thus includes a hydrocyclone plant that is much cheaper in capital expenditure and takes up less space than that
25 of the prior art because its capacity need not be as high as that of the prior art arrangements in which all stock is passed through a hydrocyclone plant. In the arrangement in accordance with the invention, it is only the stock M_1 which has come as broke that is passed through the hydrocyclone plant in the short circulation of the headbox.

The apparatus and the method in the treatment of the stock passed to the headbox of a paper machine or equivalent in accordance with the invention is characterized by what is stated in the claims.

5 In the following, the invention will be described with reference to some advantageous embodiments of the invention shown in the figures of the appended drawings, but the invention is not meant to be exclusively limited to them.

Figure 1A shows a prior art apparatus for passing stock to a headbox of a paper
10 machine.

Figure 1B shows an arrangement in accordance with the invention.

Figure 2A shows a first embodiment of the invention in which broke-containing
15 stock is passed from a first stock chest to a hydrocyclone plant, and in which embodiment the stock is passed through a wire pit.

Figure 2B shows a second embodiment of the invention.

20 Figure 3 is an illustration of principle of the operation of a hydrocyclone plant.

Fig. 1A shows a prior art stock system in which all stock $M_1 + M_2 + M_3$ is passed to a hydrocyclone plant 20, which means that a high capacity is required from the hydrocyclone plant.

25

Fig. 1B shows an arrangement in accordance with the invention. A stock chest 10a₁ contains stock, i.e. a pulp fraction M_1 , which contains broke passed from a paper machine and said pulp fraction M_1 is treated in a hydrocyclone plant 20. The cleaned stock, its accepts are passed further into connection with stocks M_2 and M_3 that do not contain broke and further to a headbox 100. The pulp fractions
30 M_2 and M_3 that do not contain broke in stock chests 10a₂ and 10a₃ thus bypass the

centrifugal cleaning 20, and the accept of the stock M_1 from the hydrocyclone plant 20 is passed into connection with said stocks M_2 and M_3 . The hydrocyclone plant 20 is not required to have as high a capacity as that of the embodiment of Fig. 1A.

5

In the embodiment of Fig. 2A, stock M_1 , or a pulp fraction, of a first stock chest 10a₁ also comprises a stock composition that requires centrifugal cleaning before it is passed to a headbox of a paper machine. The stock M_1 contains broke coming from the paper machine and, in addition, it may contain pulp coming from fibre recovery, and further mechanical pulp.

10

Stock M_2 of a second stock chest 10a₂ comprises a stock composition that has already undergone centrifugal cleaning, such as recycled fibre and/or chemical pulp and/or TMP.

15

In the embodiment of Fig. 2A, the stock M_1 is passed from the stock chest 10a₁ through a stock line a₁ to a lower part of a wire pit 11. The line a₁ includes a pump P₁. In the lower part of the wire pit, the stock M_1 is diluted with wire water obtained from a wire section of a paper machine (not shown) along a line d₁ to a consistency required by a hydrocyclone plant 20. A line a₂ leads from the lower part of the wire pit 11 to the suction side of a pump P₂ and a line a₂ leads from the pressure side of the pump P₂ to a first centrifugal cleaning step 20a₁ of the hydrocyclone plant 20 situated in the short circulation of the paper machine. In the figure, the centrifugal cleaning steps are designated with 20a₁, 20a₂, 20a₃... An accept line from the centrifugal cleaning step 20a₁ of the hydrocyclone plant 20; a line a₃ is passed further to join a line b₁ of the stock M_2 of the second stock chest 10a₂ via a mixing device 12. The mixing device 12 is also supplied with wire water from the wire pit 11 along a line e₁ for diluting the stock M_2 to be fed to the headbox 100 to a suitable consistency.

20

25

30

From the upper part of the wire pit 11 there is further a line c_1 for dilution water, said line c_1 including a pump P_3 . The line c_1 leads further from the discharge side of the pump P_3 to a deaeration tank 13a₁. The dilution water passed through the deaeration tank 13a₁ is conducted further after the deaeration treatment to a discharge line f_1 and further while pumped by a pump P_4 to a machine screen 14a₁, whose accepted fraction, i.e. accept, is passed to a dilution inlet header J_2 in the headbox 100.

The stock chest 10a₂ is provided with the line b_1 for the stock and further to the suction side of a pump P_5 . On the discharge side of the pump P_5 , the line b_1 is connected to the mixing device 12, after which there is a pump P_6 in a line b_2 for pumping the combined stock further along the line b_2 to a deaeration tank 13a₂, from which a discharge line f_2 leads further to the suction side of a pump P_7 . On the discharge side of the pump P_7 , in the line f_2 there is a machine screen 14a₂, from which an accepted fraction, i.e. accept, is passed to a stock inlet header J_1 of the headbox 100.

In the device arrangement in accordance with the invention, only the broke-containing stock M_1 passed from the stock chest 10a₁ is treated in the hydrocyclone plant 20. An accept line a_3 leads from said hydrocyclone plant further into connection with the stock line b_1 of the stock M_2 of the second stock chest 10a₂. Since the stock M_2 of the second stock chest 10a₂ comprises stock that has already previously undergone centrifugal cleaning, said line can be connected directly to the headbox 100 of the paper machine, via its deaeration tank 13a₂ and machine screen 14a₂.

In the embodiment of Fig. 2B, stock M_1 , i.e. a pulp fraction, of a first stock chest 10a₁ also comprises a stock composition that requires centrifugal cleaning before it is passed to a headbox of a paper machine. The stock M_1 contains broke coming from the paper machine and it can additionally contain pulp coming from fibre recovery and further mechanical pulp.

Stock M_2 of a second stock chest $10a_2$ comprises pulp that has already undergone centrifugal cleaning, such as recycled fibre and/or chemical pulp and/or TMP.

- 5 Also in this embodiment of the invention, only the stock M_1 passed from the stock chest $10a_1$ is treated in a hydrocyclone plant 20. In the embodiment of the figure, the stock is passed from the stock chest $10a_1$ through a line a_1 while pumped by a pump P_{10} to a mixing device 120, in which the stock is diluted to a centrifugal cleaning consistency with wire water obtained from a line f_4 , and the stock M_2 is
10 passed further through a line a_2 to the suction side of a pump P_{20} . The line a_2 on the pressure side of the pump P_{20} is connected to the hydrocyclone plant 20 to form the feed of its first centrifugal cleaning step $20a_1$.

- In the embodiment of Fig. 2B, the hydrocyclone plant 20 situated in the short
15 circulation of the paper machine includes centrifugal cleaning steps $20a_1$, $20a_2$ and $20a_3$. An accept line a_3 leads further from the first hydrocyclone, i.e. the centrifugal cleaning step $20a_1$ of the hydrocyclone plant 20 into connection with a stock line b_1 of a second stock chest $10a_2$.

- 20 In the embodiment, wire water from the paper machine is passed to a wire pit 110 through a line d_1 , which wire pit 110 in this embodiment is formed by a planar wire pit structure, a so-called flume, which comprises a horizontal flow path for wire water. Said wire pit 110 removes effectively air in bubble form from the wire water, and pre-deaeration of the wire water is accomplished by means of said wire
25 pit type. The wire water is passed from the wire pit 110 through a discharge line d_2 and a pump P_{30} to a deaeration tank $13a_3$, from which there is further a discharge line f_3 leading into connection with the line b_1 of the stock M_2 of the second stock chest $10a_2$ via a mixing device 12. The line f_4 leads further from the discharge line f_3 of the deaeration tank $13a_3$ into connection with the line a_1 of the
30 stock M_1 of the first stock chest $10a_1$ via the mixing device 120. A branch line f_5 leads further from the line f_3 to a pump P_{40} and further from the pressure side of

the pump P_{40} to a machine screen $14a_3$, which conducts the wire water further as accept from the machine screen $14a_3$ to a dilution water inlet header J_2 of a headbox 100.

- 5 The stock M_2 is passed from the stock chest $10a_2$ through a pump P_{50} along the line b_1 to the mixing device 12 in order to be combined with the stock coming as accept along the line a_3 from the hydrocyclone plant 20 and with the dilution water coming along the line f_3 . After that the diluted stock is pumped by means of a headbox feed pump P_{60} through a machine screen $14a_4$ to a stock inlet header J_1
10 of the headbox 100.

As shown in Fig. 3, the hydrocyclone plant 20 includes several centrifugal cleaning steps $20a_1$, $20a_2$, $20a_3$, so that, as shown in the figure, accept from the first step $20a_1$ is passed through the line a_3 further into connection with the line b_1
15 of the stock M_2 of the second chest $10a_2$. As shown in Fig. 3, the stock is passed through the line a_1 as a feed to the first centrifugal cleaning step of the hydrocyclone plant 20, i.e. to the hydrocyclone $20a_1$. The stock flows along a spiral-shaped path inside the hydrocyclone $20a_1$ and heavier particles separate as reject from the bottom of the hydrocyclone and lighter particles rise as accept
20 further through the line a_3 into the line b_1 of the stock M_2 passed from the second stock chest $10a_2$. There can be several hydrocyclones $20a_1$, $20a_2$, $20a_3$... and the reject from the first hydrocyclone $20a_1$ can be passed further to the second hydrocyclone $20a_2$ as its feed and the accept from it in one embodiment can be passed further to the line b_1 of the stock M_2 of the second stock chest $10a_2$.

25

The figure shows a headbox 100. The headbox 100 in accordance with the invention is advantageously a so-called dilution headbox, which means that the dilution water passed to the dilution water inlet header J_2 is passed further across the width of the headbox to different points of the stock passed from the stock
30 inlet header J_1 . In this way, dilution makes it possible to regulate the basis weight of the web across the width of the web. The dilution water passed from the

dilution water inlet header J_2 is passed to ducts which are provided with dilution water valves, by means of which the supply of dilution water can be regulated as desired across the width of the headbox, thus enabling the basis weight of the web to be regulated to be even across the entire width of the web.

5

As shown in the figure, the hydrocyclone plant can also include several accept lines, the stock passed through them being conducted into connection with another stock or with stocks passed from other chests. In accordance with the invention, it is also possible to use several stock chests, but in the invention only that stock, such as the broke-containing stock M_1 , which shall be treated in the hydrocyclone plant is circulated through the hydrocyclone plant 20. The pulp fraction M_2 which need not be cleaned with hydrocyclones is passed directly to deaeration and, after a machine screen, to the stock inlet header J_1 of the headbox 100. The accept derived from the stock M_1 in the centrifugal cleaning 20 is conducted into connection with said stock.

15

When the stocks M_1 and M_2 of the chests 10a₁, 10a₂ are referred to in this application, it is also possible to call them a pulp fraction M_1 and a pulp fraction M_2 . In this application, the paper machine is understood to mean paper, board and tissue machines.

20

The broke can be formed of paper broke, which can include trimmings or paper passed to a pulper in connection with web breaks.

25 The present application refers to lines by which are meant stock lines, pipes, ducts along which stock/wire water is passed.

Claims

1. An apparatus in the treatment of the stock passed to a headbox of a paper machine or equivalent, in which the apparatus includes at least two stock chests (10a₁, 10a₂), stock (M₁) from a first stock chest (10a₁) being passed along a line (a₁, a₂) to a hydrocyclone plant (20) in the short circulation of the paper machine or equivalent, **characterized** in that an accept line (a₃) of the hydrocyclone plant (20) is connected with a stock line (b₁) of stock (M₂) fed from a second stock chest (10a₂), and a combined stock flow is passed along a line (b₂) to the headbox (100) of the paper machine or equivalent (FIG. 2A, FIG. 2B).
2. An apparatus as claimed in claim 1, **characterized** in that the stock (M₁) in the first stock chest (10a₁) comprises a stock composition that shall be treated in the hydrocyclone plant (20).
3. An apparatus as claimed in the preceding claim, **characterized** in that the stock (M₁) in the first stock chest (10a₁) contains broke passed from the paper machine.
4. An apparatus as claimed in the preceding claim, **characterized** in that, in addition to broke pulp, the stock (M₁) contains pulp coming from fibre recovery and further mechanical pulp.
5. An apparatus as claimed in claim 1, **characterized** in that the stock (M₂) has been cleaned by hydrocyclones before passing it to the second stock chest (10a₂).
6. An apparatus as claimed in the preceding claim, **characterized** in that the stock (M₂) of the second stock chest (10a₂) contains recycled fibre and/or chemical pulp.

7. An apparatus as claimed in any one of the preceding claims, **characterized** in that the accept line (a_3) from the hydrocyclone plant (20) leads from one of its centrifugal cleaning steps ($20a_1, 20a_2, 20a_3 \dots$) to the line (b_1, b_2) of the stock (M_2) of the second stock chest ($10a_2$) (FIG. 2A).

5

8. An apparatus as claimed in any one of the preceding claims, **characterized** in that between the hydrocyclone plant (20) and the first stock chest ($10a_1$) there is a wire pit (11), from which wire water is passed to a deaeration tank ($13a_2$) and further to a machine screen ($14a_2$) and therefrom to a dilution water inlet header (J_2) (FIG. 2A).

10

9. An apparatus as claimed in any one of the preceding claims, **characterized** in that the line (a_1) from the first stock chest ($10a_1$) is connected with the wire pit (11), to which wire water is passed from the paper machine along a line (d_1), and that from the wire pit (11) there is a line (a_2) to the hydrocyclone plant (20) to form the feed of its first centrifugal cleaning step ($20a_1$), and that the line (a_1) includes a pump (P_1), and that the line (a_2) includes a pump (P_2), and that a line (C_1) for passing wire water includes a pump (P_3) for causing wire water to flow from the wire pit (11) to the deaeration tank ($13a_1$), from which there is a discharge line (f_1) for deaerated wire water, and that the line (f_1) includes a pump (P_4) from which the wire water is passed through the machine screen ($14a_1$) further to the dilution inlet header (J_2) in the headbox (100) (FIG. 2A).

15

20

10. An apparatus as claimed in any one of the preceding claims, **characterized** in that the line (b_1) from the second stock chest ($10a_2$) leads through a mixing device (12) to a line (b_2) connected to a deaeration tank ($13a_2$), from which there is a discharge line (f_2) further to a pump (P_7), the pressure side of which is connected to a machine screen ($14a_2$), and from which there is a line further to a stock inlet header (J_1) of the headbox (100) (FIG. 2A).

25

30

11. An apparatus as claimed in any one of the preceding claims, **characterized** in that from the wire pit (11) there is a line (e_1) for dilution water leading to the line (b_1) of the stock (M_2) of the second stock chest (10a₂) through the mixing device (12) (FIG. 2A).

5

12. An apparatus as claimed in any one of claims 1 to 6, **characterized** in that from the stock chest (10a₁) there is a line (a_1) to a mixing device (120), and from which there is further a line (a_2) to the first centrifugal cleaning step (20a₁) of the hydrocyclone plant (20), and that from the hydrocyclone plant (20) there is further an accept line (a_3) leading to the line (b_1) of the stock (M_2) of the second stock chest (10a₂) through a mixing device (12), and that a line (b_2) leads from the mixing device (12) to a stock inlet header (J_1) of the headbox (100), advantageously through a machine screen (14a₄), and that the line (a_1) includes a pump (P_{10}), and that the line (a_2) after the mixing device (120) includes a pump (P_{20}) (FIG 2B).

15

13. An apparatus as claimed in the preceding claim, **characterized** in that there is a line (d_1) through which wire water is passed from the paper machine to a wire pit (110), and that pre-deaeration takes place in the wire pit (110), and that there is a line (d_2) through which wire water is passed after the pre-deaeration treatment from the wire pit (110) to a deaeration tank (13a₃), from which there is further a line (f_3) for dilution water leading to the line (b_1) of the stock (M_2) of the second stock chest (10a₂), and that there is a branch line (f_4) for wire water as dilution water leading to the line (a_1) of the stock (M_1) of the first stock chest (10a₂) through the mixing device (120), and that from the line (f_3) of the deaeration tank (13a₃) there is a branch duct (f_5) to a pump (P_{40}) and further to a machine screen (14a₃) and therefrom further to the dilution water inlet header (J_2) (FIG. 2B).

20

25

14. A method in the treatment of the stock passed to a headbox of a paper machine or equivalent, in which method a first stock (M_1) is passed to a hydrocyclone plant (20) in the short circulation of the paper machine or

30

equivalent, **characterized** in that stock is passed as accept from said hydrocyclone plant (20) into connection with a second stock (M_2) and that a combined stock flow is passed to the headbox (100) of the paper machine or equivalent.

5

15. A method as claimed in claim 14, **characterized** in that stock (M_1) of a first stock chest (10a₁) which shall be treated with a hydrocyclone is used in the method.

10 16. A method as claimed in the preceding claim, **characterized** in that a stock composition containing broke passed from the paper machine is used as stock (M_1).

15 17. A method as claimed in the preceding claim, **characterized** in that stock (M_1) which, in addition to paper broke passed from the paper machine, contains pulp coming from fibre recovery and/or mechanical pulp is used in the method.

20 18. As method as claimed in any one of the preceding claims, **characterized** in that stock (M_2) of a second stock chest (10a₂), which stock has been cleaned by a hydrocyclone before passing it to the chest (10a₂), is used in the method.

19. A method as claimed in the preceding claim, **characterized** in that stock (M_2) is used that contains recycled fibre and/or chemical pulp.

1/4




FIG. 1A




FIG. 1B

2/4




FIG. 2A

3/4





FIG. 2B



INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 2004/000058

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: D21F 1/66

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: D21D, D21F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 02072948 A1 (METSO PAPER AUTOMATION OY), 19 Sept 2002 (19.09.2002), claim 1, abstract --	1-19
A	WO 02057542 A1 (METSO PAPER, INC.), 25 July 2002 (25.07.2002), abstract --	1-19
A	WO 0121885 A1 (VALMET CORPORATION), 29 March 2001 (29.03.2001), figure 4A, abstract --	1-19
A	WO 02086233 A1 (METSO PAPER, INC.), 31 October 2002 (31.10.2002), abstract -- -----	1-19



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

26 April 2004

Date of mailing of the international search report

06 -05- 2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Nils Nordin/Els
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

31/03/2004

International application No.

PCT/FI 2004/000058

WO	02072948	A1	19/09/2002	CA	2439232 A	19/09/2002
				FI	5163 U	11/12/2001
				FI	20010360 A	24/08/2002
WO	02057542	A1	25/07/2002	CA	2433331 A	25/07/2002
				EP	1346104 A	24/09/2003
				FI	20002896 A	30/06/2002
WO	0121885	A1	29/03/2001	AU	7292500 A	24/04/2001
				EP	1218587 A	03/07/2002
				JP	2003510472 T	18/03/2003
				US	6551459 B	22/04/2003
WO	02086233	A1	31/10/2002	EP	1399621 A	24/03/2004
				FI	111391 B	00/00/0000
				FI	20010830 A	24/10/2002